



TECHNICAL DATA	RR ENDURO 125 4T LC	RR MOTARD 125 4T LC
----------------	---------------------	---------------------

**CHASSIS**

Frame	steel double cradle frame	←
Wheel base	1439 mm	←
Max length	2240 mm	2192 mm
Max width	820 mm	←
Max height	1220 mm	1185 mm
Seat height	917 mm	886 mm
Ground clearance	330 mm	294 mm
Footrest height	400 mm	364 mm
Dry weight	105 kg - ant. 51,5 ; post. 53,5	←
Fuel tank capacity	7,3 l.	←
Reserve	1,5 l.	←
Front suspension	USD Hydraulic fork ø41 mm	←
Rear suspension	Monoshock with progressive compound lever	←
Shock absorber stroke	131 mm	120 mm
Front wheel travel	260 mm	240 mm
Rear wheel travel	270 mm	250 mm
Front brake	disc ø260 mm	disc ø300 mm
Rear brake	disc ø220 mm	←
Front rim	21 x 1,6 - 36 holes	17 x 2,50 - 36 holes
Rear rim	18 x 1,85 - 36 holes	17 x 3,50 - 36 holes
Front tyre	80/90-21	110/80 - 17
Rear tyre	110/80-18	130/70 - 17

**ENGINE**

Type	Single-cylinder, 4-stroke, liquid cooled	←
Bore	52,0 mm	←
Stroke	58,6 mm	←
Displacement	124,6 cc	←
Compression ratio	11,2:1	←
Ignition	Electronic 250W-14v	←
Spark plug	NGK CR8E	←
Lubrication	Forced with pump	←
Feeding	Unleaded gasoline	←
Carburettor	Keihin CVK 30	←
Clutch	Wet multi-disc clutch	←
Transmission	6 speed	←
Secondary trasmission	Z. 14/63	←
Engine oil	SAE 15W/50	←